

ORDINANCE NO. 13-193

**AN ORDINANCE LIMITING THE USE OF FIREWORKS
WITHIN THE CORPORATE LIMITS OF THE TOWN OF CORNERSVILLE**

BE IT ENACTED BY THE TOWN OF CORNERSVILLE THAT:

SECTION 1: No fireworks can be shot within the corporate limits of the Town of Cornersville between the hours of 12:00 a.m. and 8:00 a.m. anytime of the year.

SECTION 2: On the Fourth of July and New Year's Day only, no fireworks can be shot between the hours of 1:00 a.m. and 8:00 a.m.

SECTION 3: A violation of this Ordinance is a Fifty Dollar (\$50.00) fine for each occurrence.

SECTION 4: This ordinance shall be in full force and effect pursuant to and is provided in the Town of Cornersville, Tennessee Charter, Chapter 4, section 11-401.

Passed First Reading on August 1st, 2013

Passed Second Reading on September 5th, 2013



AMOS DAVIS,
MAYOR



SCOTTY BROCK,
TOWN RECORDER

APPROVED AS TO LEGALITY AND FORM;



QUINN BRANDON STEWART,
TOWN ATTORNEY

ORDINANCE NO. 13-192

AN ORDINANCE TO REPEAL AND REPLACE ORD. NO. 02-52
PERTAINING TO CULVERTS, STORM DRAINS, AND HEAD WALLS

BE IT ENACTED BY THE TOWN OF CORNERSVILLE, that Ord. No. 02-52 is repealed entirely and replaced with the following language:

1. Prior to installation or replacement of a driveway culvert or storm drain, the property owner shall consult with the Town (Town Administrator and/or Planning Commission) for determination of whether the new or replaced driveway culvert or storm drain will overload existing downstream drainage facilities. If it is determined that the downstream drainage facilities will be overloaded, the property owner shall not install or replace a driveway culvert or storm drain until adequate provisions, approved by the Town, have been made to eliminate overloading downstream drainage facilities.
2. New and replacement driveway culverts shall be a minimum diameter of 12 inches and a minimum length of 14 feet. Storm drains shall be a minimum of 18 inches.
3. Driveway culverts and storm drains shall be laid on grade with the spigot end pointing in the direction of the flow.
4. Concrete, brick or rock head walls are recommended, but not required, at both ends of driveway culverts and storm drains.

**NOW, THEREFORE, BE IT ENACTED BY THE TOWN OF
CORNERSVILLE**, that this ordinance shall be in full force and effect
pursuant to and is provided in the charter of the Town of Cornersville,
Tennessee.

Passed First Reading on August 1st, 2013.

Passed Second Reading on September 5th, 2013.

Amos Davis

AMOS DAVIS, Mayor

Scotty Brock

SCOTTY BROCK, Town Recorder

APPROVED AS TO LEGALITY AND FORM:

Quinn Stewart

QUINN STEWART, Town Attorney